



## DOUBLE DOOR FREEZER ADVANCE F 140-4 C U

Product series: Advance

Item number: 133142090

The Advance F 140-4 C U is a Double door freezer with a net internal volume of 797 liters. The outside dimensions are mm.



### DURABLE MATERIALS

The interior and exterior are made of stainless steel, the best material for humid locations. ADVANCE cabinets are designed to withstand the demanding conditions of large kitchen operations.

### MAXIMUM STORAGE SPACE

With shelves all the way from the top to the bottom of the cabinet, the inside space can be efficiently utilized for maximum produce storage.

### HYGIENE AND FOOD SAFETY

Thanks to the rounded corners and seamless surfaces, frequented cleaning routines become a quick and simple task. The practical anti-tilting shelves prevent spillage. The cabinet has a rounded base and comes with removable gaskets for easy wiping.

### MONO-BLOCK DESIGN

The ADVANCE refrigeration system uses a mono-block construction. This brings two important advantages. As the evaporator is positioned on top of the cabinet, valuable space inside the cabinet can be used for storage. Additionally, it is removable for easier maintenance and repair.

### UNIFORM KITCHEN DESIGN

The exterior of all ADVANCE cabinets features a uniform design that fits seamlessly into your Hoshizaki kitchen concept.

### TEMPERATURE STABILITY

The intelligent air distribution system allows high performance, ensuring temperature stability despite frequent door openings and during defrosting.

## SPECIFICATIONS

Product title	Double door freezer	Energy consumption (kWh/Year)	3,642
Temperature range	-25/-12°C	Energy efficiency class standard	ISO 22041-2019
Volume, gross (ltr.)	1,200	Energy efficiency class	D
Net usable volume (ltr.)	797	Energy Efficiency Index EEI	67.44
Exterior	Stainless	Sound level – dB(A)	56
Interior	Stainless	Climate class	5 (max. ambient 40°C w/ 40% RH)
Dimensions W x D x H (mm)	1344 x 830 x 1975 (including castors)	Legs / Castors	H = 125 mm (C2)
Weight, packed (kg)	198	Refrigerant (kg)	0.105
Insulation (mm)	60 (polyurethane)	CO2 equivalent (kg)	0.315
Refrigerant	R290	Tray size (mm)	2/1 GN deep
GWP	3	Maximum number of shelves	22 x 2, distance of 57 mm
Refrigeration capacity at -25°C (Watt)	674	Number of shelves	8
Power supply	230V, 50 Hz	Equipped with	One right and one left hand hinged door with lock, self closing doors, 8 grey shelves, LED lighting
Connection load (Watt)	700	Door Type	Insulated Door