

## REFRIGERATOR ADVANCE K 70-4 C DR U

Product series: Advance

Item number: 131702030

The Advance K 70-4 C DR U is a Refrigerator with a net internal volume of 415 liters. The outside dimensions are mm.

### DURABLE MATERIALS

The interior and exterior are made of stainless steel, the best material for humid locations. ADVANCE cabinets are designed to withstand the demanding conditions of large kitchen operations.

### MAXIMUM STORAGE SPACE

With shelves all the way from the top to the bottom of the cabinet, the inside space can be efficiently utilized for maximum produce storage.

### HYGIENE AND FOOD SAFETY

Thanks to the rounded corners and seamless surfaces, frequented cleaning routines become a quick and simple task. The practical anti-tilting shelves prevent spillage. The cabinet has a rounded base and comes with removable gaskets for easy wiping.

### MONO-BLOCK DESIGN

The ADVANCE refrigeration system uses a mono-block construction. This brings two important advantages. As the evaporator is positioned on top of the cabinet, valuable space inside the cabinet can be used for storage. Additionally, it is removable for easier maintenance and repair.

### UNIFORM KITCHEN DESIGN

The exterior of all ADVANCE cabinets features a uniform design that fits seamlessly into your Hoshizaki kitchen concept.

### TEMPERATURE STABILITY

The intelligent air distribution system allows high performance, ensuring temperature stability despite frequent door openings and during defrosting.



## SPECIFICATIONS

<b>Product title</b>	Refrigerator	<b>Energy consumption (kWh/Year)</b>	548
<b>Temperature range</b>	0/+10°C	<b>Energy efficiency class standard</b>	ISO 22041-2019
<b>Volume, gross (ltr.)</b>	600	<b>Energy efficiency class</b>	C
<b>Net usable volume (ltr.)</b>	415	<b>Energy Efficiency Index EEI</b>	42.41
<b>Exterior</b>	Stainless	<b>Sound level – dB(A)</b>	50
<b>Interior</b>	Stainless	<b>Climate class</b>	5 (max. ambient 40°C w/ 40% RH)
<b>Dimensions W x D x H (mm)</b>	654 x 830 x 1975 (including castors)	<b>Legs / Castors</b>	H = 125 mm (C2)
<b>Weight, packed (kg)</b>	122	<b>Refrigerant (kg)</b>	0.058
<b>Insulation (mm)</b>	60 (polyurethane)	<b>CO2 equivalent (kg)</b>	0.17
<b>Refrigerant</b>	R290	<b>Tray size (mm)</b>	2/1 GN deep
<b>GWP</b>	3	<b>Maximum number of shelves</b>	22, distance of 57 mm
<b>Ref. capacity at -10°C (Watt)</b>	361	<b>Number of shelves</b>	4
<b>Power supply</b>	230V, 50 Hz	<b>Equipped with</b>	Right hand hinged reversible door with lock, automatic door closing, 4 grey shelves, LED lighting
<b>Connection load (Watt)</b>	140	<b>Door Type</b>	Insulated Door