



DOUBLE DOOR REFRIGERATOR PREMIER K 140 C U

Product series: Premier

Item number: 171142090



The Hoshizaki PREMIER is a series of heavy-duty cabinets for energy-efficient refrigeration (Climate Class 5 (max. ambient 40°C w/ 40% RH)), catering to the needs of gastronomic perfectionists. The durable design with solid door hinges, stable stainless steel, and flawless finish is built to withstand the most demanding kitchen operations. The low-height PREMIER cabinets are customizable with castors instead of legs to easily fit into low-ceiling environments, yet convince with a surprisingly high internal volume. The Premier K 140 C U is a Double door refrigerator with a net internal volume of 1085 ltr. The dimensions are 1380 x 848 x 2075 (including castors) mm.

FOOD SAFETY & TEMPERATURE STABILITY

The efficient air circulation system helps to maintain perfect storage temperatures and to recover the inside temperature rapidly after each door opening and defrosting. The automatic defrost function ensures stable temperatures at all times. The wide, magnetic gaskets provide an effective seal.

COMPARTMENTALIZED DESIGN

The condenser is positioned on top of the cabinet, which brings multiple advantages. The cabinets can be hosed down in one run, without risking electric shortcuts. As the evaporator is positioned on top of the cabinet, valuable space inside the cabinet can be used for storage.

LOW RUNNING COSTS & SUSTAINABILITY

The energy-efficient refrigeration technology implemented in this broad line-up of storage cabinets can help save running costs on an everyday basis. The Premier K 140 C U runs on natural refrigerant and has climate class [5].

ERGONOMIC & EASY TO USE

Extras, like the practical pedal-foot door opener, allow hands-free opening, contribute to a healthier work environment, and are a real time-saver for hectic kitchen operations. The functional and intuitive display is easy to understand and use.

HYGIENE & WASTE REDUCTION

Thanks to the rounded corners, smooth surfaces, and molded rails, frequented cleaning routines become a quick and simple task. The practical anti-tilting function prevents spillage. The Interior and exterior are made of AISI 304 stainless steel and are perfectly suitable for humid locations.

EASY CUSTOMIZATION & FLEXIBILITY

Easily adjusted to your requirements, for example, the position of the door and the foot pedal. Also accommodates shelves up to 18-22 levels (4 shelves included) offering you high flexibility for different types of produce.

SPECIFICATIONS

Product title	Double door refrigerator	Energy consumption (kWh/Year)	592
Temperature range	+2/+12°C	Energy efficiency class standard	ISO 22041-2019
Volume, gross (ltr.)	1,400	Energy efficiency class	A
Net usable volume (ltr.)	1,085	Energy Efficiency Index EEI	24.75
Exterior	Stainless steel AISI 304	Sound level – dB(A)	50
Interior	Stainless steel AISI 304	Climate class	5 (max. ambient 40°C w/ 40% RH)
Dimensions W x D x H (mm)	1380 x 848 x 2075 (including castors)	Legs / Castors	H = 125 mm (C2)
Weight, packed (kg)	212	Refrigerant (kg)	0.14
Insulation (mm)	78 (polyurethane)	CO2 equivalent (kg)	0.42
Refrigerant	R290	Tray size (mm)	2/1 GN deep
GWP	3	Maximum number of shelves	22 x 2
Ref. capacity at -10°C (Watt)	361	Number of shelves	8
Power supply	230V, 50 Hz	Equipped with	One right and one left hand hinged door with lock, self closing doors and pedal door openers, 8 grey shelves, LED lighting
Connection load (Watt)	200	Door Type	Insulated Door