

## PREMIER F 70 C DR U

Product series: Premier

Item number: 173702030



The Hoshizaki PREMIER is a series of heavy-duty cabinets for energy-efficient refrigeration (Climate Class 5), catering to the needs of gastronomic perfectionists. The durable design with solid door hinges, stable stainless steel, and flawless finish is built to withstand the most demanding kitchen operations. The low-height PREMIER cabinets are customizable with castors instead of legs to easily fit into low-ceiling environments, yet convince with a surprisingly high internal volume. The Premier F 70 C DR U is a with a net internal volume of 475 ltr. The dimensions are 690 x 920 x 2075 (including castors) mm.

### FOOD SAFETY & TEMPERATURE STABILITY

The efficient air circulation system helps to maintain perfect storage temperatures and to recover the inside temperature rapidly after each door opening and defrosting. The automatic defrost function ensures stable temperatures at all times. The wide, magnetic gaskets provide an effective seal.

### COMPARTMENTALIZED DESIGN

The condenser is positioned on top of the cabinet, which brings multiple advantages. The cabinets can be hosed down in one run, without risking electric shortcuts. As the evaporator is positioned on top of the cabinet, valuable space inside the cabinet can be used for storage.

### LOW RUNNING COSTS & SUSTAINABILITY

The energy-efficient refrigeration technology implemented in this broad line-up of storage cabinets can help save running costs on an everyday basis. The Premier F 70 C DR U runs on natural refrigerant and has climate class [5].

### ERGONOMIC & EASY TO USE

Extras, like the practical pedal-foot door opener, allow hands-free opening, contribute to a healthier work environment, and are a real time-saver for hectic kitchen operations. The functional and intuitive display is easy to understand and use.

### HYGIENE & WASTE REDUCTION

Thanks to the rounded corners, smooth surfaces, and molded rails, frequented cleaning routines become a quick and simple task. The practical anti-tilting function prevents spillage. The interior and exterior are made of AISI 304 stainless steel and are perfectly suitable for humid locations.

### EASY CUSTOMIZATION & FLEXIBILITY

Easily adjusted to your requirements, for example, the position of the door and the foot pedal. Also accommodates shelves up to 18-22 levels (4 shelves included) offering you high flexibility for different types of produce.

## SPECIFICATIONS

Temperature range	-25/-5°C	Energy consumption Ecodesign AEC (kWh/Year)	1771
Volume, gross (ltr.)	700	Energy Efficiency Class (ISO 22041-2019)	C
Net usable volume (ltr.)	475	Energy Efficiency Index EEI	46.45
Exterior	Stainless steel AISI 304	Sound level – dB(A)	52
Interior	Stainless steel AISI 304	Climate class	5
Dimensions W x D x H (mm)	690 x 920 x 2075 (including castors)	Legs / Castors	H = 125 mm (C2)
Weight, packed (kg)	135	Refrigerant (kg)	0.115
Insulation (mm)	80 mm (polyurethane)	CO2 equivalent (kg)	0.345
Refrigerant	R290	GN – Shelf size	2/1 GN deep
GWP	3	Maximum number of shelves	22, distance of 57 mm
Refrigeration capacity at -25°C (Watt)	376	Number of shelves	4
Connection	230V, 50 Hz	Equipped with	Right hand hinged reversible door, automatic door closing, pedal door opener, 4 grey shelves, LED lighting
Connection load (Watt)	460	Door Type	Solid Door